

HAMILTON, BROOK, SMITH & REYNOLDS, P.C.

UTILITY PATENT APPLICATION TRANSMITTAL <small>Only for new nonprovisional applications under 37 C.F.R. 1.53(b)</small>	Attorney Docket No.	SMI-13459pA
	First Named Inventor or Application Identifier	John G. Aceti
	Express Mail Label No.	EL551543251US

Title of Invention: **DISPOSABLE MODULAR HEARING AID**

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents

ADDRESS TO: **Assistant Commissioner for Patents
Box Patent Application
Washington, D.C. 20231**

- | | |
|---|--|
| <p>1. <input type="checkbox"/> Fee Transmittal Form
<i>(Submit an original, and a duplicate for fee processing)</i></p> <p>2. <input checked="" type="checkbox"/> Specification [Total Pages 1-37]
<i>(preferred arrangement set forth below)</i></p> <ul style="list-style-type: none"> - Descriptive title of the invention - Cross References to Related Applications - Statement Regarding Fed sponsored R & D - Reference to microfiche Appendix - Background of the Invention - Summary of the Invention - Brief Description of the Drawings - Detailed Description - Claim(s) - Abstract of the Disclosure <p>3. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) [Total Sheets 1/24-24/24]
 <input type="checkbox"/> Formal <input checked="" type="checkbox"/> Informal</p> <p>4. <input type="checkbox"/> Oath or Declaration/POA [Total Pages []]</p> <ul style="list-style-type: none"> a. <input type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 C.F.R. 1.63(d))
 <i>(for continuation/divisional with Box 17 completed)</i>
 [NOTE Box 5 below] <ul style="list-style-type: none"> i. <input type="checkbox"/> <u>DELETION OF INVENTOR(S)</u>
 Signed statement attached deleting
 inventor(s) named in the prior application,
 see 37 C.F.R. 1.63(d)(2) and 1.33(b). <p>5. <input type="checkbox"/> Incorporation By Reference <i>(useable if Box 4b is checked)</i> The
 entire disclosure of the prior application, from which a copy of the
 oath or declaration is supplied under Box 4b, is considered as
 being part of the disclosure of the accompanying application and
 is hereby incorporated by reference therein.</p> | <p>6. <input type="checkbox"/> Microfiche Computer Program <i>(Appendix)</i></p> <p>7. <input type="checkbox"/> Nucleotide and/or Amino Acid Sequence Submission
 (if applicable, all necessary)</p> <ul style="list-style-type: none"> a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy (identical to computer copy)
 [] Pages c. <input type="checkbox"/> Statement verifying identity of above copies |
|---|--|

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & documents)
9. ☐ 37 C.F.R. 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document *(if applicable)*
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application, status
still proper and desired
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☐ Other: _____

17. **If a CONTINUING APPLICATION**, check appropriate box and supply the requisite information:
- ☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.:
- Prior application information: Examiner: Group Art Unit:

18. CORRESPONDENCE ADDRESS

NAME	Leo R. Reynolds, Esq.				
	HAMILTON, BROOK, SMITH & REYNOLDS, P.C.				
ADDRESS	Two Militia Drive				
CITY	Lexington	STATE	MA	ZIP CODE	02421-4799
COUNTRY	USA	TELEPHONE	(781) 861-6240	FAX	(781) 861-9540

Signature		Date	3/13/00
Submitted by Typed or Printed Name	Leo R. Reynolds	Reg. Number	20,884

LRR/JJD/asb(dab)
03/13/00

1-

Date: <u>3-13-00</u>	Express Mail Label No. <u>EL55154325145</u>
----------------------	---

Inventors: John G. Aceti, Marvin A. Leedom, Frederick Fritz, Derek
D. Mahoney, John M. Margicin, Walter P. Sjursen,
Michael H. Tardugno and David A. Preves

Attorney's Docket No.: SMI-13459pA

DISPOSABLE MODULAR HEARING AID

RELATED APPLICATION

This application claims the benefit of U.S. Provisional Application No.
60/132,593, filed May 5, 1999, the entire teachings of which are incorporated herein by
5 reference and claims the benefit of U.S. Provisional Application No. 60/157,813, filed
October 6, 1999, the entire teachings of which are incorporated herein by reference.

This application is related to copending U.S. Applications:

ATTORNEY DOCKET NO..	TITLE
2506.1005-001	Mass Produced Hearing Aid With a Limited Set of Acoustical Formats
10 2506.1013-001	One-Size-Fits-All Uni-Ear Hearing Instrument
2506.2008-001	Hearing Aid
2506.2012-000	Hearing Aid With Flexible Shell
2506.2013-000	Hearing Aid Prescription Selector
2506.2014-000	Through-Hole and Surface Mount Technologies for Highly-Automatable Hearing Aid Receivers
15 2506.2019-000	Remote Programming and Control Means for a Hearing Aid

all filed of even date herewith, the entire teachings of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

Hearing aids are delicate electro-acoustical devices that are intended to perform flawlessly in the harsh environment of the human ear. Hearing aid manufacturers use hard durable earmold materials to protect the delicate electronics and transducers from adverse conditions in and out of the ear. Such durable materials are intended to survive a greater than four year usage life. The earmold can be used not only to protect the internal components of the hearing aid, but also to form an interface between the electronics and the ear canal. This interface must be created to prevent acoustical feedback, to retain the electronics in the ear and prevent irritation or fatigue of the ear canal. A design conflict for the earmold can then exist between the need to have a soft, pliant, nonirritating and comfortable material, and the need to have a durable material to protect the internal electronic components which can last more than four years.

A disposable hearing aid is one designed to have a useful life of much less than the traditional four years. The useful life of a disposable hearing aid can also be governed by the life of the battery. If the battery can be replaced, the hearing aid is no longer disposable and the advantages of the disposable aid are lost. However, a number of other variants on the disposable aid are possible. These variants look to maintain the advantages of disposability while making the system more convenient, comfortable, longer lasting or providing better performance.

“One-size-fits-all” type hearing aids generally lack a flexibility of their tips. Such a lack of flexibility prevents deep penetration into the bony region of an ear canal by the hearing aid. Such hearing aids are also unable to create an acoustic seal in the ear canal. Without such penetration or such a seal in the bony region, the hearing aid can create an occlusion effect in the wearer. Also, hearing aids lacking a proper acoustic seal are prone to feedback.

Feedback is a nagging, unsolved problem for hearing aid manufacturers and dispensers. Feedback in a hearing aid is present in several forms: electrical, acoustical and mechanical. While electrical feedback is more easily controllable with additional circuitry, the latter two forms of feedback in hearing aids remain significant problems that often reduce the effectiveness of hearing aid fittings. Acoustical or mechanical feedback signals from the hearing aid receiver may be transduced by the hearing aid microphone, amplified in the circuitry and output from the receiver again but with higher gain, creating a feedback loop, and potentially oscillation. A criteria by Nyquist states that a system will oscillate if the gain of the open loop transfer function at a particular frequency is greater than unity and its phase shift of the open loop transfer function is a multiple of 360 degrees. Acoustical feedback occurs through the air inside of the hearing aid housing as well as on the outside of the hearing aid while it is being worn. Mechanical feedback occurs because of the receiver vibrating the hearing aid housing. Hearing aid designers have used many techniques to prevent the creation of such feedback loops. Included are rubber isolation mounts for the microphone and receiver, stiff tubes on the receiver output port and electronically filtering the hearing aid output to suppress energy at the most likely to be troublesome feedback frequencies. Unfortunately, hearing aids frequently have feedback oscillation frequencies in the very range at which the wearer requires amplification most, such as in the frequency range between 1500 and 5000 Hz.

SUMMARY OF THE INVENTION

One possible solution to the conflict between comfort and durability of the earmold is the creation of a disposable hearing aid which uses ultra soft earmold materials that may not last over a four year period, but can be mass produced in an economically competitive manner. The earmold can therefore be replaced more frequently than the disposable hearing aid. An earmold that is replaced on a more frequent basis than the replacement cycle of the disposable aid can provide a user with benefits. If the earmold is replaced on a daily basis, as compared to a base unit which is

replaced after a much longer period of time than the earmold, the user can be provided with a high degree of comfort, cleanliness, and performance.

Earmold tip flexibility is necessary to allow for deep ear canal insertion of a hearing aid to overcome the convolutions present in a typical ear canal. An earmold having a flexible tip incorporated with the earmold can have several advantages. These advantages include potentially deep ear canal fittings, efficient coupling of the sound emitted from the receiver to the ear drum, and a corresponding reduction in the required output levels of the receiver. The flexible tip can also provide a comfortable fit even for cases where the tip is located in the bony region of the ear canal. It is observed that when the tip creates a seal in this bony region, the occlusion effect is substantially mitigated.

The compliance of an earmold tip of a hearing aid is also important in hearing aid design. If the earmold tip is compliant enough, the tip can fit into many different sizes and shapes of ear canals. A desirable tip is one that slides easily into the bony structure of the ear canal, feels comfortable and provides a good acoustic seal.

The present invention relates to a modular hearing aid having a replaceable base unit adapted to contain any of a microphone, a receiver, a battery, electronics and controls and a replaceable earmold removably attached to the base unit, the earmold having a compliant material and a retention mechanism for connection to the base unit. Alternately, the modular hearing aid can include a base unit adapted to contain any of a microphone, a receiver, electronics and controls and a replaceable earmold removably attached to the base unit, the earmold having a battery integrated with the earmold. The earmold can have a shell integrated with the earmold, the shell housing the battery.

A modular hearing aid can also have a base unit having any of a microphone, electronics and controls and an earmold where the earmold can include both a receiver and a battery integrated with the earmold. The earmold can also have a shell integrated with the earmold, where the shell houses the receiver and the battery. A modular hearing aid can also have a base unit having any of a microphone, battery, electronics and

controls and an earmold having a shell and a receiver where the earmold houses the receiver. Alternately, in this embodiment, the shell of the earmold houses the receiver.

The earmold can form an earmold tip for attachment to a distal end of the base unit, an earmold sleeve for attachment to at least a portion of the base unit or an earmold tip and an earmold sleeve for attachment to the base unit.

The present invention also relates to a modular hearing aid having a replaceable base unit adapted to contain any of a microphone, a receiver and a battery, an earmold removably attached to the base unit, the earmold having a compliant material and a retention mechanism for connection to the base unit and a module comprising a shell and electronics, the module removably connected to the earmold and the base. The earmold can include a battery removably attached to the earmold. The module can have a receiver. The earmold can also have a battery integrated with the earmold and the module can have a receiver or a microphone.

The earmold can form an earmold tip for attachment to a distal end of the base unit. The earmold can also form an earmold sleeve for attachment to at least a portion of the base unit. The earmold can also form an earmold tip and an earmold sleeve for attachment to the base unit.

The invention can also include a modular hearing aid having a base unit adapted to contain a microphone, a receiver, electronics and controls and an earmold tip integrated with a battery and removably attached to the base unit, the earmold tip having a compliant material and a retention mechanism for connection to the base unit such that the earmold tip can be connected to the base unit or removed from the base unit and replaced after use.

The invention can also relate to a method for replacing an earmold of a modular hearing aid having the steps of providing a modular hearing aid having a base unit and an earmold, releasing a securing mechanism between the earmold and the base unit, removing the earmold from the base unit, discarding the earmold, placing a second earmold onto the base unit and attaching the securing mechanism. The invention can also relate to a method for replacing a base unit of a modular hearing aid having the

steps of providing a modular hearing aid having a base unit and an earmold, releasing a securing mechanism between the earmold and the base unit, removing the base unit from the earmold, discarding the base unit, placing a second base unit onto the earmold and attaching the securing mechanism. The invention can also relate to a method for

5 replacing a component of a modular hearing aid having the steps of providing a modular hearing aid having a base unit component, an earmold component and a module component, releasing at least one securing mechanism among the earmold component, base unit component and module component, removing a component from the modular hearing aid, discarding the component, replacing the component and attaching the at

10 least one securing mechanism among the earmold component, base unit component and module component.

A flexible earmold tip for a hearing aid can have a vibration isolator portion. A mushroom shaped tip portion for insertion into an ear canal and a sound bore can be formed between the vibration isolator portion and the mushroom shaped tip portion.

15 The vibration isolator portion includes a receiver having a diaphragm adapted to vibrate in operation creating acoustical vibrations which cause the receiver to mechanically vibrate. The vibration isolation portion attenuates such mechanical vibrations from the receiver. The vibration isolation portion mechanically decouples the receiver from a hearing aid base unit to isolate the mechanical vibrations of the receiver from the base

20 unit.

The sound bore includes a spring and a compliant material surrounding the sound bore where the spring prevents collapsing of the sound bore and controls the flexibility of the flexible earmold tip. The flexible earmold tip includes an outlet port which allows collection of earwax without clogging the sound bore. The hearing aid, to

25 which the flexible earmold tip is attached, includes a base unit in which is mounted a microphone. The mushroom shaped tip portion creates a seal with an ear canal to acoustically isolate a hearing aid base unit from acoustical vibrations created by the receiver. The vibration isolation portion can include a nest in which the receiver sits to

acoustically seal the receiver within the vibration isolation portion thereby acoustically isolating the hearing aid base unit from the acoustical vibrations created by the receiver.

A hearing aid and tip assembly can include a hearing aid base unit having a microphone, a battery and electronics, and a flexible earmold tip having a vibration
5 isolator portion, a mushroom shaped tip portion and a sound bore. The vibration isolator portion is enclosed by the base unit and includes a receiver electrically attached to the base unit where the receiver includes a diaphragm adapted to vibrate in operation causing the receiver to mechanically vibrate. The vibration isolation portion attenuates vibrations from the receiver. The mushroom shaped tip portion is attached to the
10 vibration isolator portion. The sound bore is formed between the vibration isolator portion and the mushroom shaped tip portion and provides a channel for the transfer of sound from the receiver to an ear canal of a user.

The sound bore includes a spring and a compliant material surrounding the sound bore where the spring prevents collapsing of the sound bore and controls the
15 flexibility of the flexible earmold tip. The flexible earmold tip can also include an outlet port which allows collection of earwax without clogging the sound bore. The vibration isolation portion can mechanically decouple the receiver from the base unit to isolate the mechanical vibrations of the receiver from the base unit. The mushroom shaped tip portion can create a seal with an ear canal to acoustically isolate the hearing
20 aid base unit from acoustical vibrations created by the receiver. The vibration isolation portion comprises a nest in which the receiver sits to acoustically seal the receiver within the vibration isolation portion thereby acoustically isolating the base unit from acoustical vibrations created by the receiver.

Feedback can be attenuated within a hearing aid by providing a hearing aid base
25 unit, a receiver, and a hearing aid tip having a flexible mushroom shaped tip portion and vibration isolator portion. Surrounding the receiver with the vibration isolator portion attenuates acoustic vibrations and mechanical vibrations created by the receiver during operation. Securing the vibration isolator portion and receiver within the hearing aid base unit further mechanically decouples the receiver from the base unit. Placing the

hearing aid within an ear causes the mushroom shaped tip portion to form a seal with the ear canal to attenuate acoustic vibrations produced by the receiver.

A hearing aid can also include a base unit having an inside portion and adapted to contain any of a microphone, a receiver, a battery, electronics and controls and a
5 potting material which pots at least a portion of the inside portion of the base unit. The material increases the mass of the hearing aid and attenuates vibrations created by the receiver during operation. The potting material can also increase the stiffness of the base unit, thereby raising its resonant frequencies above the typical feedback oscillation frequency range to reduce feedback in the hearing aid. The potting material can include
10 an epoxy. The hearing aid can be disposable.

Feedback can be reduced in a hearing aid by providing a hearing aid having an inside portion adapted to contain any of a microphone, a receiver, a battery, electronics and controls and potting at least a portion of the inside portion of the hearing aid with a material, thereby increasing the mass of the hearing aid. The increased mass of the
15 hearing aid attenuates vibrations created by the receiver during operation and reduces feedback in the hearing aid.

A disposable hearing aid can include a hearing aid portion, a flexible core and a compliant tip portion. The hearing aid portion includes a shell containing a battery, a receiver, a microphone and electronics. The flexible core attaches to the hearing aid
20 portion and forms a sound bore to allow sound produced by the hearing aid portion to travel to the ear canal. The compliant tip portion is adapted to be inserted into an ear canal, surrounds the flexible core and forms an acoustic seal in the ear canal. The tip material can include layers of fingers surrounding the flexible core. The layers of fingers can be made from an elastomer material. The tip material can also include a
25 fluid-filled bladder surrounding the flexible core. The fluid-filled bladder can have air within the bladder or can have liquid within the bladder. The fluid-filled bladder can also have a flexible bladder wall to allow for flexibility of the fluid-filled bladder to accommodate size changes within the ear canal.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other objects, features and advantages of the invention will be apparent from the following more particular description of preferred embodiments of the invention, as illustrated in the accompanying drawings in which like reference

5 characters refer to the same parts throughout the different views. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the invention.

Figure 1 illustrates an embodiment of a modular hearing aid having a replaceable earmold.

10 Figure 2 illustrates an alternate embodiment of the hearing aid of Figure 1, the hearing aid having a battery integral with an earmold.

Figure 3A shows an alternate embodiment of the hearing aid of Figure 1, the hearing aid having a battery and an earmold integral with a shell.

15 Figure 3B shows an alternate embodiment of the hearing aid of Figure 1, the hearing aid having a battery, a receiver and an earmold integral with a shell.

Figure 4A illustrates a hearing aid having an integral earmold and shell, the shell housing a receiver.

Figure 4B illustrates a hearing aid having an integral earmold and shell, the earmold housing a receiver.

20 Figure 5 illustrates an alternate embodiment of the hearing aid of Figure 1, the hearing aid having a replaceable earmold integrated with a shell having a battery and receiver.

Figure 6 illustrates an alternate embodiment of the hearing aid of Figure 1, the hearing aid having a receiver incorporated with the earmold.

25 Figure 7 illustrates an alternate embodiment of the hearing aid of Figure 6.

Figure 8 illustrates an alternate embodiment of the hearing aid of Figure 1 where the replaceable earmold incorporates a portion of the shell.

Figure 9 shows an alternate embodiment of the hearing aid of Figure 1 where the earmold allows the replacement of an integral shell and electronics module.

Figure 10 shows an alternate embodiment of the hearing aid of Figure 1 where the earmold allows the replacement of an integral shell, electronics and receiver module.

Figure 11 illustrates an alternate embodiment of the hearing aid of Figure 1 where the hearing aid has a base unit, a replaceable shell module and a replaceable
5 earmold integrated with a battery.

Figure 12 illustrates an alternate embodiment of the hearing aid of Figure 11.

Figure 13 shows an alternate embodiment of the hearing aid of Figure 11.

Figure 14 illustrates a top view of a flexible earmold tip for a hearing aid.

Figure 15 illustrates a side view of a flexible earmold tip for a hearing aid.

10 Figure 16 illustrates a front view of a flexible earmold tip for a hearing aid.

Figure 17 and 18 shows a cross-sectional view of a flexible earmold tip.

Figure 19 shows a cross-sectional view of a hearing aid having a flexible earmold tip as illustrated in Figures 14-16.

Figure 20 shows a hearing aid having a flexible earmold tip as illustrated in
15 Figures 14-16.

Figures 21-24 illustrate a disposable hearing aid having a compliant tip.

DETAILED DESCRIPTION OF THE INVENTION

An embodiment of a modular hearing aid 10 is shown in Figure 1. The modular hearing aid 10 can have an earmold 12 and a base unit 36. The base unit 36 can be a
20 rigid or semi-rigid structure to which the earmold is attached or which holds and aligns other internal components. In one embodiment, the base unit 36 can be a core 14 having a shell 16. In a preferred embodiment both the earmold 12 and the base unit 36 can be replaced by the user after use. The earmold 12 can be replaced on a more frequent basis than the base unit 36.

25 The earmold 12 can have three preferred embodiments in any given embodiment of the modular hearing aid 10. In one embodiment, the earmold 12 forms an earmold tip 18. The earmold tip 18 can be made from an ultra soft and compliant material. The material can be an injection moldable, biocompatible thermoelastomer, such as C-flex

(Consolidated Polymer Technologies, Inc., Largo, FL). The material, in a preferred embodiment, can be a castable, biocompatible silicone polymer, such as PlatSil (Polytek Development Corporation, Easton, PA). The earmold tip can also attach to a distal end of the shell 16 and extend into an ear canal. In another embodiment, the earmold 12
5 forms an earmold sleeve 20. The earmold sleeve 20 can be made from an ultra soft and compliant material. The earmold sleeve 20 can also cover a portion or all of the base unit 36. In a third embodiment, as shown in Figure 1, the earmold 12 forms an earmold tip 18 and sleeve 20. In this embodiment, the tip 18 and sleeve 20 can be made from an ultra soft and compliant material. The tip 18 and sleeve 20 can also cover a portion or
10 all of the shell 16 and can extend into the ear canal.

The earmold 12 can be formed such that it firmly holds onto the core 16 by a retention mechanism. The retention mechanism can be a mechanical snap, mechanical twist-lock or friction, for example.

The modular hearing aid 10 can also include a microphone, a receiver,
15 electronics and controls. The electronics can include an integrated circuit and passive components. The controls can include an on-off control and a volume control. In one embodiment, these components are located within the core 14. The modular hearing aid can also have a battery.

In an alternate embodiment of the hearing aid with replaceable earmold 10, the
20 earmold 12 can include a battery 22, as shown in Figure 2. The battery 22 integrated with the earmold 12 includes an electrical connection to the base unit 36. The battery 22 can include contacts 24 which connect to the core 14. In this embodiment, the earmold 12 and battery 22 are provided as a single unit, which is replaceable on the hearing aid core 14. Frequent replacement of the battery 22 and earmold 12 can provide
25 a user with an optimum level of comfort, cleanliness, performance and economy. Integrating the battery 22 with the earmold 12, the battery 22 can be more easily handled by the user because the integrated battery and earmold are larger than the battery alone.

The combined earmold 12 and battery 22 can form an ear mold tip 18, an ear mold sleeve 20 or an ear mold tip 18 and sleeve 20, similar to that described above. The earmold 12 and battery 22 can be retained on the core 14 by mechanical snap or friction, for example. The contacts 24 of the battery 22 can also be used to retain the combined
5 earmold 12 and battery 22, to the core 14.

Figure 3A illustrates an embodiment of a modular hearing aid 10 having a replaceable earmold 12, shell 15 and battery 22 formed as one integral unit. This unit can act as a covering for a hearing aid base unit. The battery 22 integrated with the earmold 12 includes an electrical connection to the base unit 36. The components of a
10 hearing aid that can be replaced or are preferably replaced are the battery 22, the earmold 12 and the shell 15. The battery 22 can be replaced because batteries generally lose their powering ability after a certain amount of use. The earmold 12 and the shell 15 can be replaced because the components contacts the ear canal and can require frequent cleaning.

15 This embodiment of the modular hearing aid 10 can have a base unit 36 which can include a microphone 30, electronics 28 and a receiver 26. The earmold 12 and shell 15 integral with the battery 22 can be mechanically or frictionally attached to the non-replaceable base unit 36. The base unit 36 can fit within the shell 15 for attachment. The battery 22 can have contacts 24 which can connect to the base unit 36.
20 When the contacts 24 of the battery 22 are mated to the base unit 36, current can flow from the replaceable battery 22 to the electronics 28 in the base unit 36. The contacts 24 of the battery 22 can also be used to retain the integrated earmold 12 and battery 22 to the base unit 36.

Figure 3B illustrates another embodiment of the modular hearing aid 10 where
25 the earmold 12 and shell 15 are integrated with a battery unit 22 and a receiver 26. In this embodiment, the hearing aid 10 can also have a base unit 36 having a microphone 30 and electronics 28. The battery 22 integrated with the earmold 12 includes an electrical connection to the base unit 36. In this embodiment, the earmold 12, shell 15, battery 22 and receiver 26 are integrated into a single unit that can act as a covering for

a base unit 36 and that the unit can be replaced more frequently than the base unit 36, which may or may not be disposable. This provides convenience, cleanliness and product longevity to the user.

5 The receiver 26 can be incorporated into the replaceable earmold 12 and shell 15 for two reasons. First, the receiver 26 is preferably placed deep into the ear canal in order to achieve the highest effective sound pressure levels possible. For many types of hearing aids, the earmold 12 also protrudes deeply in the ear canal to guide and position the electronics 28 and receiver 26. Therefore integrating the receiver with the earmold 12 and shell 15 allows placement of the receiver deep into the ear canal.

10 Second, the receiver 26 can be incorporated into the replaceable earmold 12 and shell 15 because it is very prone to damage if the modular hearing aid 10 is dropped from a height of several feet onto a hard surface. By integrating the receiver 36 with the replaceable earmold 12 and shell 15, replacement of a damaged receiver 36 is easily performed by a user. Being able to replace the receiver after damage can add longevity
15 to the unit 10.

Figure 4A shows an embodiment of a modular hearing aid 10 having a replaceable earmold 12, shell 15 and receiver 26, formed as one unit, where the shell 15 houses the receiver 26. The unit can act as a covering for a hearing aid base unit. The components of a hearing aid that can be replaced or are preferably replaced are the
20 receiver 26, the earmold 12 and the shell 15. The receiver 26 can be easily replaced by a user when the receiver 36 is damaged. The earmold 12 and the shell 15 can be replaced because the components contacts the ear canal and can require frequent cleaning.

This embodiment of the modular hearing aid 10 can have a base unit 36 which
25 can include a microphone 30, electronics 28 and a battery 22. The earmold 12 and shell 15 integral with the receiver 26 can be mechanically or frictionally attached to the non-replaceable base unit 36. The base unit 36 can fit within the shell 15 for attachment. The receiver 26 can electrically connect to the base unit 36.

Figure 4B shows another embodiment of a modular hearing aid 10 having a replaceable earmold 12, shell 15 and receiver 26, formed as one unit, where the earmold 12 houses the receiver 26. The unit can act as a covering for a hearing aid base unit. Similar to the hearing aid 10 described above, the modular hearing aid 10 can have a base unit 36 which can include a microphone 30, electronics 28 and a battery 22. The earmold 12 having the receiver 26 and the shell 15 can be mechanically or frictionally attached to the non-replaceable base unit 36. The base unit 36 can fit within the shell 15 for attachment and the receiver 26 can electrically connect to the base unit 36.

Figures 3A, 3B, 4A and 4B illustrate the earmold 12 as having an earmold tip 18. As shown, the earmold tip 18 has a mushroom shaped design. Such a design can aid in securing the modular hearing aid 10 within a user's ear. The mushroom shaped design can also provide comfort, ease of insertion and sound attenuation. The mushroom shaped tip can be made from a low modulus, low durometer material, such as silicone. Such a material allows the mushroom shaped tip to be flexible and compliant. The earmold tip 18 having a mushroom shaped design can be used with all embodiments of the modular hearing aid 10.

Figure 5 illustrates an alternate embodiment of the modular hearing aid 10 where the replaceable earmold 12 is integrated with a shell 48 having a battery 22 and receiver 26. Some hearing aid shapes would benefit from a better design if the shell 48 was replaceable. For example, most in-the-canal (ITC) and completely-in-the-canal (CIC) hearing aids have receivers which are acoustically and mechanically sealed to a shell. These hearing aids would realize the benefits of a replaceable receiver section only if the shell 48 was replaced. By integrating the earmold 12 with a shell containing a battery 22 and receiver 26, in this embodiment, the shell 48 is replaceable with the earmold 12.

This embodiment can have a base unit 36 having a microphone 30 and electronics 28. The base unit 36 can have base unit connectors 40 which allow for electrical contact between a receptacle section 42 and the base unit 36. In a preferred embodiment, power (battery) and signal (receiver) conductors are required. The

earmold 12 integral with the shell 48, having the battery 22 and receiver 26, can be mechanically or frictionally attached to the non-replaceable base unit 36. The mechanical attachment can be a snap fit.

Figures 6 and 7 show embodiments of the hearing aid 10 where a receiver 26 is incorporated with the earmold 12. In one embodiment, shown in Figure 6, the earmold 12 and receiver 26 are incorporated as an integral and replaceable unit but the earmold 12 is defined as a tip section 18 only. In another embodiment, shown in Figure 7, the earmold 12 is defined as a tip 18 and a sleeve 20. In either embodiment, the modular hearing aid 10 can have a base unit 36 which can include a shell 50, a microphone 30, a battery 22 and electronics 28.

The advantages of having a replaceable earmold 12 and receiver 26 have been described above. In this embodiment, the battery 22 within the base unit 36 can be replaced, but is not integrated into the earmold 12. The earmold 12 integral with the receiver 26 can be mechanically or frictionally attached to the base unit 36. The receiver 26 can have contacts 32 which can provide an electrical connection to the base unit 36 and allow the passage of signal from the base unit 36 to the receiver 26. The contacts 32 of the receiver 26 can also be used to retain the integrated earmold 12 to the base unit 36.

In another embodiment, the base unit 36 can have a base unit shell 50 and an earmold shell 52 where the earmold shell 52 can be integrated with the earmold 12, as shown in Figure 8. In this embodiment, the integrated earmold 12 and shell 52, as well as the battery 22, can be replaced. The battery 22, however, is preferably not integrated with the earmold 12 and shell 52. The integrated earmold 12 and shell 52 can also include a replaceable receiver 26. The hearing aid 10 can also have a base unit 36 which can include a microphone 30, electronics 28 and a shell 50. The base unit shell 50 and the earmold shell 52 include an attachment mechanism which allows each shell to be joined together. The attachment mechanism can include a flexible integral snap having two joinable portions, a first portion molded to the base unit shell 50 and a second portion molded to the earmold shell 52. The attachment mechanism can also

include screw threads between the shell 50 and earmold shell 52 to allow for the attachment of the shell 50 to the earmold shell 52. The attachment mechanism can create a seal between the base unit shell 50 and the earmold shell 52. The seal protects the internal performance of the hearing aid and minimizes internal acoustical feedback.

5 One advantage of this embodiment is that the user can independently replace either the integrated earmold 12 and shell 52 combination or the battery 22, as required. The battery 22 can be replaced at the end of its useful life. The integrated earmold 12 and shell 52 can be replaced for sanitary, cleanliness or performance reasons.

 No electrical connections are needed between the earmold 12 and shell 52
10 combination. The integrated earmold 12 and shell 52 combination can be mechanically or frictionally attached to the non-replaceable base unit 36, as earlier defined.

 The battery 22 and receiver 26 can have electrical connections within the modular hearing aid 10. The battery 22 can be electrically connected to the electronics 28 and can provide power to the hearing aid 10. In a preferred embodiment, the battery
15 22 is held within the hearing aid 10 by a clip. The receiver 26 can also be electrically connected to the electronics 28. In a preferred embodiment, the receiver 26 is electrically connected to the electronics 28 by spring conductors.

 Figure 9 illustrates an alternate embodiment of a replaceable earmold 12 which allows the replacement of an integrated shell and electronics module 54 as a separate
20 component of the earmold 12. The modular hearing aid 10, in a preferred embodiment, can include the earmold 12 having the shell and electronics module 54 and can also include a replaceable battery 22 connected to the shell and electronics module 54 and a non-replaceable base unit 36 having a microphone 30 and a receiver 26.

 The battery 22 can be replaced at the end of its useful life. The shell and
25 electronics module 54 and the earmold 12 are not integrated. The earmold 12 can be replaced separately from the shell and electronics module 54 for the purpose of cleanliness, sterility, and performance. In one embodiment, the earmold 12 can be replaced on a daily basis. For peak performance and maximum unit longevity, this embodiment also encompasses the replacement of the integral shell and electronics

module 54. As electronic components continue to improve faster than improvements to transducer technology, it can be advantageous to replace the electronics 28 and, in particular, the hearing aid's 10 integrated circuit, independent of the transducers. This disclosure defines an integrated shell and electronics module 54 where the shell 55, in a preferred embodiment, is a convenient and protective means for mounting the electronics 28. The shell 55 can provide both electrical and mechanical connection and attachment means for the electronics 28. The shell 55 can provide the electronics 28 with a frictional attachment with the earmold 12 and with an electrical connection to the receiver 26 of the base unit 36 and the battery 22.

10 Figure 10 shows another embodiment of the modular hearing aid 10 having a base unit 36, a replaceable earmold 12 and a replaceable shell 58 which integrates electronics 28 and a receiver 26 into a single module 56. The base unit 36 can include a microphone 30 and a battery 22. In this embodiment, the earmold 12 is separately replaceable from the shell, electronics and receiver module 56.

15 The battery 22 and receiver 26 can have electrical connections within the modular hearing aid 10. The battery 22 in the base unit 36 can be electrically connected to the electronics 28 in the module 56. The receiver 26 can also be electrically connected to the electronics 28. In a preferred embodiment, the receiver 26 is electrically connected to the electronics 28 by spring conductors.

20 This embodiment combines the advantages of a modular hearing aid 10 having a non-replaceable base unit 36 with the advantages of a replaceable receiver 26. The integration of the electronics 28 and the receiver 26 in a separate replaceable shell module 46 allows the user to replace the electronics 28 and receiver 26 in the hearing aid 10, simultaneously, as needed.

25 Figures 11, 12 and 13 show embodiments for a modular hearing aid 10 where the hearing aid 10 has a base unit 36, a replaceable shell module 46 having electronics 28 and a replaceable earmold 12 integrated with a battery 22. In each embodiment, the earmold 12 can be separately replaced for the purpose of cleanliness, sterility, and performance. The battery 22 in a hearing aid can be replaced at the end of its useful life.

The battery 22 integrated with the earmold 12 can include an electrical connection to the base unit 36. By integrating the replaceable earmold 12 with the battery 22, a user can simultaneously provide himself with a sterile covering and a fresh power source for a modular hearing aid 10. The electronics 28 of the module 46 can be electrically
5 connected to the base unit 36. The electronics 28 of the module 46 can also be electrically connected to the battery 22 integrated with the earmold 12. Also in each embodiment, the shell module 46 can be replaced separately from the integrated earmold 12 and battery 22 combination.

In the embodiment of Figure 11, the base unit 36 can have a microphone 30 and
10 a receiver 26 and the replaceable shell module 46 can have a shell 59 and electronics 28. The integration of the electronics 28 in a separate replaceable shell module 46 allows the user to replace only the electronics 28, as is needed. For example, as electronic components continue to improve faster than improvements to transducer technology, it can be advantageous to replace the electronics 28 of a hearing aid independent of the
15 transducers.

In the embodiment shown in Figure 12, the base unit 36 can have a microphone 30 and the replaceable shell module 46 can have a shell 59, electronics 28 and a receiver 26. The integration of the electronics 28 and the receiver 26 in a separate replaceable shell module 46 allows the user to replace the electronics 28 and receiver 26 in the
20 hearing aid 10, simultaneously, as needed.

In the embodiment of Figure 13, the base unit can have a receiver 26 and the replaceable shell module 46 can have a shell 59, a microphone 30 and electronics 28. The integration of the electronics 28 and the microphone 30 in a separate, replaceable shell module 46 allows the user to replace the electronics 28 and microphone 30 in the
25 hearing aid 10 simultaneously, as is needed.

The invention can also include a method for replacing an earmold of a modular hearing aid. In this method, a modular hearing aid having a base unit and an earmold can first be provided. Next a securing mechanism between the earmold and the base unit can be released. This allows the separation of the earmold and the base unit. The

earmold can then be removed from the base unit, discarded and replaced with a second earmold onto the base unit. This allows a user to place a clean or fresh earmold onto an existing base unit. The earmold can then be attached to the base unit with the securing mechanism.

- 5 In an alternate method, the base unit of a modular hearing aid can be replaced. In this method, a modular hearing aid having a base unit and an earmold can first be provided. Next a securing mechanism between the earmold and the base unit can be released. This allows the separation of the earmold and the base unit. The base unit can then be removed from the earmold, discarded and replaced with a second base unit.
- 10 This allows a user to replace a non-functioning or malfunctioning base unit with a working base unit. The base unit can then be attached to the ear mold with the securing mechanism.

- In another method, a component of a modular hearing aid can be replaced. In this method a modular hearing aid having a base unit component, an earmold
- 15 component and a module component can be provided. Next, at least one securing mechanism can be released among the earmold component, base unit component and module component. Next a component can be removed from the modular hearing aid, discarded and replaced. The at least one securing mechanism can then be attached among the earmold component, base unit component and module component.

- 20 Figures 14, 15 and 16 show an earmold tip 60 which has an integral mushroom shaped tip portion 62 and integral vibration isolator portion 64. The earmold tip 60 can provide comfort, ease of insertion, sound attenuation, and can help to anchor the unit in an ear.

- The flexible earmold tip 60 can be constructed from a soft, low durometer
- 25 material, such as silicone, and can be produced by a cast molding process for inexpensive manufacture. The soft material can provide comfort to the wearer, while generating an acceptable acoustic seal between the hearing aid and ear. Because the earmold tip 60 is constructed of a low modulus, low durometer material, the earmold tip

60 provides a high level of comfort for users even when the tip 60 is located in the bony region of the ear.

Figure 16 shows an outlet port 68 which has been recessed to essentially provide a mechanism for collecting wax without clogging a sound bore 74. An integral
5 membrane can also be deployed in the outlet port 68 to serve as a wax guard. Such a wax collection mechanism can also aid in providing comfort to a user. Also shown is a sound bore 74. The sound bore 74 connects the mushroom shaped tip portion 62 to the vibration isolator portion 64 and carries sound created by a receiver to an ear canal. The sound bore 74 has a rectangular cross-sectional shape. During manufacture of the tip
10 60, a spring 70 is placed around the sound bore 74 prior to the casting of the compliant material over the spring 70. The rectangular cross-sectional area of the sound bore 74 can help to maintain the position of the spring 70 during casting of the tip 60. Therefore, the sound bore 74 is surrounded not only by the spring 70 but by the compliant material which forms the tip 60. The sound bore 74 can have a cross-
15 sectional area such that the bore 74 increases high frequency acoustical transmission from a receiver 26 to a user's ear canal. In this respect, the sound bore 74 can help match the impedance of the ear canal to the receiver 26. The sound bore 74 can also include a proximal sound bore portion 80 having a circular cross-sectional area. The circular cross-sectional area of the proximal portion 80 provides a transition between the
20 rectangular cross-sectional area of the sound bore 74 and a receiver 26.

The mushroom shaped tip portion 62 has an optimum tip diameter 72 within the range of 6 to 12 mm, with 8 to 10 mm diameter tips fitting most individuals, while a 9 mm diameter tip being the ideal diameter. Several internal features of the mushroom shaped tip portion 62 are shown in the cut-away view of Figure 17. The mushroom
25 shaped tip portion 62 includes a spring 70 which can be formed integral with the earmold tip 60. The spring 70 can have a stiffness value that is consistent with a desired tip flexibility. For example, the stiffer the spring, the less flexible the mushroom shaped tip portion 62 relative to the vibration isolator portion 64. The spring 70 can also act to prevent the collapse of the sound bore 74 during bending. Alternately, a stiff material

can be used to surround the sound bore 74, which can allow the tip 60 to flex but not collapse. The spring 70 can have an open coil construction which permits the flow of material between coils during the manufacturing process so as to retain the spring 70 in the earmold tip 60. Finally, with respect to the spring 70, the longitudinal

- 5 compressibility of the spring 70 can enhance comfort during insertion into an ear canal of a user.

The vibration isolator 64 acts to retain the earmold tip 60 in the body of a hearing aid instrument, which results in a permanently mounted tip 60. The vibration isolator 66 includes a conical shape which can help secure the earmold tip 60 within the
10 hearing aid. Adhesives can also be used to help retain the tip in the hearing aid.

The vibration isolator 64 also acts to secure hearing aid components. The vibration isolator can include a nest 66 which houses and covers a receiver 26, as shown in Figure 18. Alternately, the receiver 26 can be partially housed and covered by the vibration isolator 64. An adhesive can be used to secure and acoustically seal the
15 receiver to the earmold tip 60. Once the receiver 26 is seated in its nest 66, the earmold tip 60 becomes more secure because of the subassembly created by the tip and receiver 26 combination. The receiver 26 is a relatively rigid component that is confined in the vibration isolator 64 and enclosed by the hearing aid. The permanent mounting of the earmold tip 60 to the hearing aid can alleviate the potential hazards associated with tip
20 detachment in the ear.

The vibration isolation properties of the earmold tip 60 are due largely to the compliance of the tip material. Because of the compliance, the vibration isolator 64 can mechanically decouple the receiver 26 from the hearing aid. To illustrate, the receiver 26 includes a diaphragm such that when the receiver 26 generates sound, the diaphragm
25 vibrates. The vibration of the diaphragm can, in turn, vibrate the receiver 26 itself. When a receiver 26 is rigidly mounted to a hearing aid, vibrations of the receiver 26 vibrate the hearing aid and its shell. Vibration of the hearing aid can create feedback within the hearing aid. Mechanical decoupling of the receiver 26 from the hearing aid can reduce this feedback phenomenon. The compliant hearing aid tip 60 absorbs

vibrations from the receiver 26 caused by the vibration of the diaphragm within the receiver. The tip 60 therefore isolates the mechanical vibrations of the receiver 26 from the hearing aid, thereby mechanically decoupling each portion. To obtain an effective isolator, one must consider the mass of the object, such as the receiver, that is to be
5 decoupled. By lowering the resonant frequency of receiver/nest system, the receiver vibrations are highly attenuated.

In addition to vibration isolation, the tip 60 provides sufficient acoustic isolation to attenuate unwanted feedback and associated oscillations during operation. Part of the isolation is obtained from a seal produced by the mushroom shaped tip 62 in
10 conjunction with a given ear canal. Such a seal can produce an external acoustic isolation from external acoustic vibration for the hearing aid. For example, the receiver of the hearing aid sends sound to an ear drum. If the sound vibrations travel from the receiver and around the hearing aid and into the microphone of the hearing aid, feedback will result. A tip 60 having a mushroom shaped tip portion 62 can provide a
15 seal which prevents sound vibrations from traveling around the hearing aid to the microphone. The feedback path from the output of the receiver to the microphone is attenuated by the mushroom shaped tip.

To prevent the sound from the receiver 26 from leaking internally to the microphone 30, soft material, by way of the isolation nest 66, can completely surround
20 the receiver thereby attenuating internal acoustic vibrations transmitted from the receiver 26 to the microphone 30. Without the presence of acoustic isolation of the receiver 26, as the receiver 26 produces sound, the sound can leak from the output of the receiver 26, around the receiver 26, and back to the microphone 30 within the hearing aid itself. Such a sound leak can create feedback oscillations. Surrounding the receiver
25 26 with a compliant material, such as the nest 66, can eliminate any spaces around the receiver 26 through which sound can travel. The compliant material surrounding the receiver 26 acts as a gasket to provide a good acoustic seal for the receiver, thereby providing internal acoustic isolation. Alternately, to create internal acoustic isolation,

the soft material could partially enclose the receiver, with an adhesive used to complete the seal.

Figures 19 and 20 show the tip 60 mounted in a hearing aid 78. Figure 19 shows a hearing aid base unit having internal components, such as a battery 22, microphone 30, and electronics 28. The earmold tip 60 is mounted within the base unit such that the receiver can electronically connect to the electronics 28. Figure 20 depicts an assembled hearing aid 78. The hearing aid 78 includes a hearing aid base unit 80 and a tip 60. The tip 60 is clamped between two half-shell portions of the hearing aid base unit 80.

Mechanical feedback in a hearing aid can also be reduced by potting the inside of hearing aid with a material that increases the mass of the hearing aid. Potting the inside of the hearing aid can embed the components of the hearing aid, such as a receiver, a microphone, electronics, controls and a battery, within a material. The potting material can form an acoustical barrier inside the hearing aid between the receiver and the microphone. The material can also be used to pot a portion of the inside of the hearing aid base unit. The potting material used to reduce mechanical and acoustical feedback can be epoxy, for example.

An increase in mass of the hearing aid can help to attenuate vibrations created by the receiver during operation, thereby preventing the vibrations from being conducted to a portion of the hearing aid shell near the hearing aid microphone and causing mechanical feedback oscillation. The increase in mass can also reduce acoustical feedback by creating a blocking wall so as to prevent the acoustical vibration energy created by the receiver from traveling through air inside the hearing aid housing. The potting material can also increase the stiffness of the base unit, thereby raising its resonant frequencies above the typical feedback oscillation frequency range to reduce feedback in the hearing aid.

Potting the inside of a hearing aid to prevent the transmission of mechanical vibration and acoustical energy has not been performed previously. A hearing aid which is potted renders any required repairs on the hearing aid as very expensive, since

the repairer would have to work through the potting material to reach the components to be repaired or replaced. Therefore, by virtue of a hearing aid being potted, the hearing aid must be disposed once a component of the hearing aid has failed. If the hearing aid is intended to be disposable, potting is an effective solution to feedback problems.

5 Figures 21-24 illustrate a disposable hearing aid having a compliant tip 90. The disposable hearing aid with a compliant tip 90 includes a hearing aid 92 having a hard shell, which contains the battery and all of the electronics, and a compliant tip 94 that can penetrate deep into an ear canal and is attached to the hearing aid 92 by a flexible core 96.

10 The compliant tip 94 can consist of many layers of thousands of tiny fingers 98 arranged around a flexible core 96, as shown in Figures 21 and 22. The fingers 98 can be made from a soft elastomer such as silicone rubber, for example. The fingers 98 can also be formed into a round or rectangular cross section, shown in Figure 22. When the fingers 98 of the tip 94 slide into an irregular shaped ear canal, the fingers 98 can bend,
15 twist, or interleave to form an acoustic seal to separate an inner and outer area of the ear canal. The flexible core 96 at the center of the fingers 98 of the tip 94 is hollow, thereby forming a sound bore 100. The sound bore 100 allows amplified sound to pass through the tip 94 to the inner ear. The flexible core 96 can accommodate any angle change in the ear canal while the fingers 98 can accommodate any size or shape change in the ear
20 canal.

 The compliant tip 94 can also consist of a fluid filled bladder 102 around the flexible center core, as shown in Figures 23 and 24. The bladder can have a donut-like shape. The fluid within the bladder 102 can be air or liquid, for example. If the bladder 102 is filled with air, when the tip 94 is placed within an ear canal and the tip 94 is
25 deformed, the air can compress and force the thin bladder walls 104 to stretch to accommodate various ear canal shapes and sizes. If the bladder 102 is filled with a liquid, such as water, the water will flow to accommodate shape changes of the canal. However, when liquid is used to fill the bladder 102, the walls 104 of the bladder 102 must be flexible enough to stretch to accommodate size changes. The liquid can contain

a jelling agent to prevent any feeling of liquid sloshing in the user. The fluid filled bladder 102 can fill a void smoothly, rather than buckle like solid rubber rings when the rings enter a cavity which is much smaller than the diameter of the ring.

While this invention has been particularly shown and described with references
5 to preferred embodiments thereof, it will be understood by those skilled in the art that
various changes in form and details may be made therein without departing from the
scope of the invention encompassed by the appended claims.

CLAIMS

What is claimed is:

1. A modular hearing air comprising:
a base unit adapted to contain any of a microphone, a receiver, a battery,
5 electronics and controls, and wherein the base unit can be replaced after use; and
an earmold removably attached to the base unit, the earmold comprising
a compliant material and comprising a retention mechanism for connection to
the base unit such that the earmold can be connected to the base unit or removed
10 from the base unit and replaced after use on a more frequent basis than the
replacement of the base unit.
2. A modular hearing air comprising:
a base unit adapted to contain any of a microphone, a receiver,
electronics and controls; and
an earmold removably attached to the base unit, the earmold comprising
15 a compliant material, a retention mechanism for connection to the base unit such
that the earmold can be connected to the base unit or removed from the base unit
and replaced after use, and the earmold comprising a battery integrated with the
earmold.
3. The modular hearing aid of Claim 2 wherein the earmold further comprises a
20 shell integrated with the earmold, the shell housing the battery.
4. A modular hearing air comprising:
a base unit adapted to contain any of a microphone, electronics and
controls; and
an earmold removably attached to the base unit, the earmold comprising
25 a compliant material, a retention mechanism for connection to the base unit such

that the earmold can be connected to the base unit or removed from the base unit and replaced after use, and the earmold comprising both a battery and a receiver integrated with the earmold.

5. The modular hearing aid of Claim 4 wherein the earmold further comprises a shell integrated with the earmold, the shell housing the battery and the receiver.
6. A modular hearing air comprising:
 - a base unit adapted to contain any of a microphone, a battery, electronics and controls; and
 - an earmold removably attached to the base unit, the earmold comprising a compliant material, a retention mechanism for connection to the base unit such that the earmold can be connected to the base unit or removed from the base unit and replaced after use, and the earmold comprising a receiver and a shell, the shell integrated with the earmold and the receiver housed within the shell.
7. The modular hearing aid of Claim 6 wherein the receiver is integrated with the earmold.
8. The modular hearing aid of Claim 1 wherein the earmold forms an earmold tip for attachment to a distal end of the base unit.
9. The modular hearing aid of Claim 1 wherein the earmold forms an earmold sleeve for attachment to at least a portion of the base unit.
10. The modular hearing aid of Claim 1 wherein the earmold forms an earmold tip and an earmold sleeve for attachment to the base unit.
11. A modular hearing aid comprising:

a base unit adapted to contain any of a microphone, a receiver, a battery and controls;

an earmold removably attached to the base unit, the earmold comprising a compliant material and comprising a retention mechanism for connection to the base unit such that the earmold can be connected to the base unit or removed from the base unit and replaced after use; and

a module comprising a shell and electronics, the module removably connected to the earmold and removably connected to the base unit such that the module can be disconnected from the base unit and the earmold and replaced after use.

12. The modular hearing aid of Claim 11 wherein the earmold further comprises a battery removably attached to the earmold.

13. The modular hearing aid of Claim 11 wherein the module further comprises a receiver.

14. The modular hearing aid of Claim 11 wherein the earmold further comprises a battery integrated with the earmold.

15. The modular hearing aid of Claim 14 wherein the module further comprises a receiver.

16. The modular hearing aid of Claim 14 wherein the module further comprises a microphone.

17. The modular hearing aid of Claim 11 wherein the earmold forms an earmold tip for attachment to a distal end of the base unit.

18. The modular hearing aid of Claim 11 wherein the earmold forms an earmold sleeve for attachment to at least a portion of the base unit.
19. The modular hearing aid of Claim 11 wherein the earmold forms an earmold tip and an earmold sleeve for attachment to the base unit.
- 5 20. A modular hearing air comprising:
a base unit adapted to contain a microphone, a receiver, electronics and controls; and
an earmold comprising a compliant material integrated with a battery, the earmold having a flexible, mushroom shaped earmold tip and comprising a retention mechanism for connection to the base unit such that the earmold can be connected to the base unit or removed from the base unit and replaced after use.
- 10
21. A modular hearing aid comprising:
a base unit adapted to contain a microphone and electronics; and
an earmold comprising a compliant material integrated with a battery and a receiver, the earmold having a flexible, mushroom shaped earmold tip and comprising a retention mechanism for connection to the base unit such that the earmold can be connected to the base unit or removed from the base unit and replaced after use.
- 15
22. A method for replacing an earmold of a modular hearing aid comprising the steps:
providing a modular hearing aid having a base unit and an earmold;
releasing a securing mechanism between the earmold and the base unit;
removing the earmold from the base unit;
discarding the earmold;
placing a second earmold onto the base unit; and
- 20
- 25

attaching the securing mechanism.

23. A method for replacing a base unit of a modular hearing aid comprising the steps:

5 providing a modular hearing aid having a base unit and an earmold;
releasing a securing mechanism between the earmold and the base unit;
removing the base unit from the earmold;
discarding the base unit;
placing a second base unit onto the earmold; and
attaching the securing mechanism.

- 10 24. A method for replacing a component of a modular hearing aid comprising the steps:

providing a modular hearing aid having a base unit component, an
earmold component and a module component;
15 releasing at least one securing mechanism among the earmold
component, base unit component and module component;
removing a component from the modular hearing aid;
discarding the component;
replacing the component; and
attaching the at least one securing mechanism among the earmold
20 component, base unit component and module component.

25. A flexible earmold tip for a hearing aid comprising:

a vibration isolator portion adapted for attachment within a hearing aid,
the vibration isolator portion having a receiver disposed therein and wherein the
receiver includes a diaphragm adapted to vibrate in operation creating acoustical
25 vibrations which cause the receiver to mechanically vibrate and wherein the

vibration isolation portion attenuates such mechanical vibrations from the receiver.

26. The flexible earmold tip of Claim 25 further comprising a mushroom shaped tip portion for insertion into an ear canal, the mushroom shaped tip portion attached to the vibration isolator portion.
27. The flexible earmold tip of Claim 26 wherein the mushroom shaped tip portion creates a seal with an ear canal to acoustically isolate a hearing aid base unit from the acoustical vibrations.
28. The flexible earmold tip of Claim 26 further comprising a sound bore coupling the vibration isolator portion to the mushroom shaped tip portion.
29. The flexible earmold tip of Claim 28 wherein the sound bore comprises a spring and a compliant material surrounding the sound bore wherein the spring prevents collapsing of the sound bore and controls the flexibility of the flexible earmold tip.
30. The flexible earmold tip of Claim 25 wherein the flexible earmold tip further comprises an outlet port which allows collection of earwax without clogging the sound bore.
31. The flexible earmold tip of Claim 25 wherein the vibration isolation portion mechanically decouples the receiver from a hearing aid base unit to isolate the mechanical vibrations of the receiver from the base unit.
32. The flexible earmold tip of Claim 25 wherein the hearing aid includes a base unit in which is mounted a microphone.

33. The flexible earmold tip of Claim 25 wherein the hearing aid includes a base unit in which is mounted a microphone and the vibration isolation portion comprises a nest in which the receiver sits to acoustically seal the receiver within the vibration isolation portion thereby acoustically isolating the base unit from the acoustical vibrations created by the receiver.
34. The flexible earmold tip of Claim 25 wherein the vibration isolator portion partially covers the receiver.
35. The flexible earmold tip of Claim 34 further comprising an adhesive wherein the adhesive secures and acoustically seals the receiver to the earmold.
36. A hearing aid comprising:
- a hearing aid base unit having a microphone, a battery and electronics; and
 - a flexible earmold tip having a vibration isolator portion, a mushroom shaped tip portion and a sound bore, the vibration isolator portion enclosed by the base unit and having a receiver electrically attached to the base unit wherein the receiver includes a diaphragm adapted to vibrate in operation causing the receiver to mechanically vibrate and wherein the vibration isolation portion attenuates vibrations from the receiver, the mushroom shaped tip portion being attached to the vibration isolator portion, and the sound bore formed between the vibration isolator portion and the mushroom shaped tip portion and the sound bore providing a channel for the transfer of sound from the receiver to an ear canal of a user.
37. The hearing aid of Claim 36 wherein the sound bore comprises a spring and a compliant material surrounding the sound bore wherein the spring prevents

collapsing of the sound bore and controls the flexibility of the flexible earmold tip.

- 5 38. The hearing aid of Claim 36 wherein the flexible earmold tip further comprises an outlet port which allows collection of earwax without clogging the sound bore.
39. The hearing aid of Claim 36 wherein the vibration isolation portion mechanically decouples the receiver from the base unit to isolate the mechanical vibrations of the receiver from the base unit.
- 10 40. The hearing aid of Claim 36 wherein the mushroom shaped tip portion creates a seal with an ear canal to acoustically isolate the hearing aid base unit from acoustical vibrations created by the receiver.
- 15 41. The hearing aid of Claim 36 wherein the vibration isolation portion comprises a nest in which the receiver sits to acoustically seal the receiver within the vibration isolation portion thereby acoustically isolating the base unit from acoustical vibrations created by the receiver.
- 20 42. A method for attenuating feedback in a hearing aid comprising:
 providing a hearing aid base unit, a receiver, and a hearing aid tip having a flexible mushroom shaped tip portion and vibration isolator portion;
 surrounding the receiver with the vibration isolator portion to attenuate acoustic vibrations and mechanical vibrations created by the receiver during operation; and
 securing the vibration isolator portion and receiver within the hearing aid base unit.

43. The method of Claim 42 further comprising placing the hearing aid within an ear such that the mushroom shaped tip portion forms a seal with the ear canal to attenuate acoustic vibrations produced by the receiver.
44. A hearing aid comprising:
- 5 a base unit having an inside portion, the base unit adapted to contain any of a microphone, a receiver, a battery, electronics and controls; and
- a potting material which pots at least a portion of the inside portion of the base unit, wherein the material increases the mass of the hearing aid and wherein the material attenuates vibrations created by the receiver during
- 10 operation.
45. The hearing aid of Claim 44 wherein the hearing aid is disposable.
46. The hearing aid of Claim 44 wherein the potting material forms an acoustical barrier inside the hearing aid between the receiver and the microphone.
47. A method for reducing feedback in a hearing aid comprising:
- 15 providing a hearing aid having an inside portion adapted to contain any of a microphone, a receiver, a battery, electronics and controls;
- potting at least a portion of the inside portion of the hearing aid with a material, thereby increasing the mass of the hearing aid;
- attenuating vibrations created by the receiver during operation through
- 20 the increased mass of the hearing aid; and
- reducing feedback in the hearing aid by attenuating vibrations created by the receiver.
48. A disposable hearing aid comprising:

a hearing aid portion wherein the hearing aid portion comprises a shell containing a battery, a receiver, a microphone and electronics;

a flexible core attached to the hearing aid portion, the flexible core forming a sound bore, thereby allowing sound produced by the hearing aid portion to travel to the ear canal; and

a compliant tip portion adapted to be inserted into an ear canal, wherein the tip portion surrounds the flexible core and wherein the tip portion forms an acoustic seal in the ear canal.

49. The disposable hearing aid of Claim 48 wherein the tip material comprises layers of fingers surrounding the flexible core.
50. The disposable hearing aid of Claim 49 wherein the layers of fingers comprise an elastomer material.
51. The disposable hearing aid of Claim 48 wherein the tip material comprises a fluid-filled bladder surrounding the flexible core.
52. The disposable hearing aid of Claim 51 wherein the fluid-filled bladder comprises air within the bladder.
53. The disposable hearing aid of Claim 51 wherein the fluid-filled bladder comprises liquid within the bladder.
54. The disposable hearing aid of Claim 51 wherein the fluid-filled bladder further comprises a flexible bladder wall to allow for flexibility of the fluid-filled bladder to accommodate size changes within the ear canal.
55. A covering for a hearing aid comprising:

- 5 56. The covering of Claim 55 wherein the covering further comprises a receiver.
57. A covering for a hearing aid comprising:
- an earmold comprising a compliant material;
 - a shell integrated with the earmold wherein the shell allows the
 - attachment of a hearing aid base unit; and
 - 10 a receiver mounted within the covering.

DISPOSABLE MODULAR HEARING AID

ABSTRACT OF THE DISCLOSURE

5 The present invention relates to a modular hearing aid having a base unit and a detachable earmold. A battery, an earmold tip and a receiver can be integrated with the earmold. The earmold can also include a removably attached module. The module can have a shell, electronics, a receiver or a microphone. A hearing aid also includes a flexible hearing aid tip having a vibration isolator portion and a mushroom shaped tip portion. The vibration isolator portion mechanically decouples a receiver from a
10 hearing aid base unit while the mushroom shaped tip portion provides an acoustic seal in the ear canal of a user. The internal components of a hearing aid can be potted to attenuate vibrations created by the receiver during operation.

1




Figure 1

Variable	Mean	Standard Deviation	Minimum	Maximum
Age	34.5	10.2	22	55
Gender	0.5	0.5	0	1
Marital Status	0.6	0.5	0	1
Education	12.5	1.5	10	16
Income	3500	1500	1000	8000
Health	0.8	0.2	0	1
Smoking	0.3	0.5	0	1
Alcohol	0.2	0.4	0	1
Exercise	0.4	0.5	0	1
Stress	0.6	0.5	0	1
Sleep	0.7	0.3	0	1
Diet	0.5	0.5	0	1
Work	0.8	0.2	0	1
Family	0.6	0.5	0	1
Friends	0.7	0.4	0	1
Hobbies	0.5	0.5	0	1
Travel	0.4	0.5	0	1
Shopping	0.6	0.5	0	1
Reading	0.5	0.5	0	1
TV	0.7	0.4	0	1
Music	0.6	0.5	0	1
Gardening	0.4	0.5	0	1
Cooking	0.5	0.5	0	1
Cleaning	0.6	0.5	0	1
Driving	0.7	0.4	0	1
Volunteering	0.3	0.5	0	1
Religion	0.5	0.5	0	1
Politics	0.4	0.5	0	1
Environment	0.6	0.5	0	1
Technology	0.7	0.4	0	1
Art	0.5	0.5	0	1
Sports	0.6	0.5	0	1
Traveling	0.4	0.5	0	1
Shopping	0.5	0.5	0	1
Reading	0.6	0.5	0	1
TV	0.7	0.4	0	1
Music	0.6	0.5	0	1
Gardening	0.4	0.5	0	1
Cooking	0.5	0.5	0	1
Cleaning	0.6	0.5	0	1
Driving	0.7	0.4	0	1
Volunteering	0.3	0.5	0	1
Religion	0.5	0.5	0	1
Politics	0.4	0.5	0	1
Environment	0.6	0.5	0	1
Technology	0.7	0.4	0	1
Art	0.5	0.5	0	1
Sports	0.6	0.5	0	1
Traveling	0.4	0.5	0	1
Shopping	0.5	0.5	0	1
Reading	0.6	0.5	0	1
TV	0.7	0.4	0	1
Music	0.6	0.5	0	1
Gardening	0.4	0.5	0	1
Cooking	0.5	0.5	0	1
Cleaning	0.6	0.5	0	1
Driving	0.7	0.4	0	1
Volunteering	0.3	0.5	0	1
Religion	0.5	0.5	0	1
Politics	0.4	0.5	0	1
Environment	0.6	0.5	0	1
Technology	0.7	0.4	0	1
Art	0.5	0.5	0	1
Sports	0.6	0.5	0	1
Traveling	0.4	0.5	0	1
Shopping	0.5	0.5	0	1
Reading	0.6	0.5	0	1
TV	0.7	0.4	0	1
Music	0.6	0.5	0	1
Gardening	0.4	0.5	0	1
Cooking	0.5	0.5	0	1
Cleaning	0.6	0.5	0	1
Driving	0.7	0.4	0	1
Volunteering	0.3	0.5	0	1
Religion	0.5	0.5	0	1
Politics	0.4	0.5	0	1
Environment	0.6	0.5	0	1
Technology	0.7	0.4	0	1
Art	0.5	0.5	0	1
Sports	0.6	0.5	0	1
Traveling	0.4	0.5	0	1
Shopping	0.5	0.5	0	1
Reading	0.6	0.5	0	1
TV	0.7	0.4	0	1
Music	0.6	0.5	0	1
Gardening	0.4	0.5	0	1
Cooking	0.5	0.5	0	




Figure 2




Figure 3A

1. General Information	
2. Name	3. Address
4. City	5. State
6. Zip	7. Phone
8. Date	9. Time
10. Subject	11. Topic
12. Author	13. Title
14. Editor	15. Publisher
16. Year	17. Price
18. Pages	19. Format
20. Binding	21. Condition
22. Notes	23. Remarks
24. Comments	25. Signature
26. Initials	27. Stamp
28. Mark	29. Seal
30. Label	31. Tag
32. Card	33. Slip
34. Sheet	35. Page
36. Volume	37. Issue
38. Part	39. Section
40. Chapter	41. Article
42. Entry	43. Item
44. Record	45. Document
46. File	47. Folder
48. Box	49. Shelf
50. Rack	51. Cabinet
52. Room	53. Building
54. Campus	55. City
56. State	57. Country
58. Continent	59. World
60. Universe	61. Cosmos
62. Galaxy	63. Star
64. Planet	65. Moon
66. Comet	67. Asteroid
68. Meteor	69. Satellite
70. Rocket	71. Space
72. Ship	73. Boat
74. Plane	75. Car
76. Train	77. Bus
78. Ship	79. Boat
80. Plane	81. Car
82. Train	83. Bus
84. Ship	85. Boat
86. Plane	87. Car
88. Train	89. Bus
90. Ship	91. Boat
92. Plane	93. Car
94. Train	95. Bus
96. Ship	97. Boat
98. Plane	99. Car
100. Train	101. Bus




Figure 4A



Figure 4B

005460" 99942560




Figure 5




Figure 6

	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2433	2434	2435	2436	2437	2438	2439	2440	2441	2442	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---




Figure 7




Figure 8

1




Figure 9

1



1

1	1	1	1
2	2	2	2
3	3	3	3
4	4	4	4
5	5	5	5
6	6	6	6
7	7	7	7
8	8	8	8
9	9	9	9
10	10	10	10
11	11	11	11
12	12	12	12
13	13	13	13
14	14	14	14
15	15	15	15
16	16	16	16
17	17	17	17
18	18	18	18
19	19	19	19
20	20	20	20
21	21	21	21
22	22	22	22
23	23	23	23
24	24	24	24
25	25	25	25
26	26	26	26
27	27	27	27
28	28	28	28
29	29	29	29
30	30	30	30
31	31	31	31
32	32	32	32
33	33	33	33
34	34	34	34
35	35	35	35
36	36	36	36
37	37	37	37
38	38	38	38
39	39	39	39
40	40	40	40
41	41	41	41
42	42	42	42
43	43	43	43
44	44	44	44
45	45	45	45
46	46	46	46
47	47	47	47
48	48	48	48
49	49	49	49
50	50	50	50
51	51	51	51
52	52	52	52
53	53	53	53
54	54	54	54
55	55	55	55
56	56	56	56
57	57	57	57
58	58	58	58
59	59	59	59
60	60	60	60
61	61	61	61
62	62	62	62
63	63	63	63
64	64	64	64
65	65	65	65
66	66	66	66
67	67	67	67
68	68	68	68
69	69	69	69
70	70	70	70
71	71	71	71
72	72	72	72
73	73	73	73
74	74	74	74
75	75	75	75
76	76	76	76
77	77	77	77
78	78	78	78
79	79	79	79
80	80	80	80
81	81	81	81
82	82	82	82
83	83	83	83
84	84	84	84
85	85	85	85
86	86	86	86
87	87	87	87
88	88	88	88
89	89	89	89
90	90	90	90
91	91	91	91
92	92	92	92
93	93	93	93
94	94	94	94
95	95	95	95
96	96	96	96
97	97	97	97
98	98	98	98
99	99	99	99
100	100	100	100




Figure 11




Figure 12

Figure 13




Figure 14

Variable	Mean	SD	Min	Max
Age	34.5	10.2	21	55
Gender	Male	Female		
Marital status	Married	Single		
Education	High school	College		
Occupation	Manager	Worker		
Income	\$10,000	\$20,000		
Health status	Good	Fair		
Exercise frequency	Weekly	Monthly		
Stress level	Low	High		
Sleep quality	Good	Poor		
Dietary habits	Healthy	Unhealthy		
Alcohol consumption	None	Occasional		
Tobacco use	Non-user	User		
Family size	2	3		
Home ownership	Owner	Renter		
Commute time	15 min	30 min		
Work hours	40 hrs	50 hrs		
Job satisfaction	High	Low		
Life satisfaction	High	Low		
Overall health	Good	Fair		





Figure 15

11



Figure 16




[illegible]

Figure 18

Figure 1 is a perspective view of a shoe sole assembly. The sole is divided into a heel portion (60) and a forefoot portion (78). A heel cap (80) is shown on the heel portion.

Figure 20




Figure 21




Figure 22

Variable	Mean	SD	Min	Max
Age	34.5	10.2	18	65
Gender	0.5	0.5	0	1
Marital status	0.6	0.5	0	1
Education	12.5	1.5	9	16
Income	1500	500	500	3000
Health status	0.8	0.2	0	1
Smoking status	0.3	0.5	0	1
Alcohol consumption	0.2	0.4	0	1
Exercise frequency	0.5	0.5	0	1
Stress level	0.7	0.3	0	1
Sleep quality	0.6	0.4	0	1
Work satisfaction	0.5	0.5	0	1
Life satisfaction	0.6	0.4	0	1
Depression score	0.3	0.5	0	1
Anxiety score	0.2	0.4	0	1
Resilience score	0.7	0.3	0	1
Optimism score	0.6	0.4	0	1
Gratitude score	0.5	0.5	0	1
Forgiveness score	0.4	0.5	0	1
Compassion score	0.3	0.5	0	1
Kindness score	0.2	0.4	0	1
Generosity score	0.1	0.3	0	1
Patience score	0.4	0.5	0	1
Self-control score	0.3	0.5	0	1
Emotional stability score	0.6	0.4	0	1
Empathy score	0.5	0.5	0	1
Empowerment score	0.4	0.5	0	1
Self-efficacy score	0.3	0.5	0	1
Resilience score	0.7	0.3	0	1
Optimism score	0.6	0.4	0	1
Gratitude score	0.5	0.5	0	1
Forgiveness score	0.4	0.5	0	1
Compassion score	0.3	0.5	0	1
Kindness score	0.2	0.4	0	1
Generosity score	0.1	0.3	0	1
Patience score	0.4	0.5	0	1
Self-control score	0.3	0.5	0	1
Emotional stability score	0.6	0.4	0	1
Empathy score	0.5	0.5	0	1
Empowerment score	0.4	0.5	0	1
Self-efficacy score	0.3	0.5	0	1




Figure 23




Figure 24